

150,000 / then every 300,000

SERVICE AT A GLANCE MAINTENANCE INTERVALS

FOR PINNACLE[™], GRANITE[®], TERRAPRO[®], AND ANTHEM[™] MANUFACTURED YEAR 2022 GHG AND NEWER

| | | Economy Duty Greater than 7.5 mpg Less than 31L/100km | Normal Duty Greater than 6 mpg Less than 39L/100km | Heavy Duty Greater than 5 mpg Less than 50L/100km | Severe Duty Less than 5 mpg Greater than 50L/100km | | |
|--|-------|--|---|--|---|--|--|
| ENGINE | | | | | | | |
| MACK PREMIUM ENGINE OIL, FILTERS AND FUEL FILTERS | | | | | | | |
| Manufactured Year 2022 GHG and Newer Engines Using Mack EOS-5 Oil Specifications NOTE: Mack cannot be held responsible for problems caused by non-genuine filters that do not meet Mack performance or durability requirements. *Mack Engine Oil EOS-5 / **Other Mack Approved EOS-5 Oil | | | | | | | |
| MP7 / MP8 Oil Pan: Mack EOS-5, Filters and Fuel Filters (Replace) If idle time is greater than 30%, use the next lower drain interval. | Miles | 75,000* / 55, 000** | 60,000* / 55,000** | 45,000* / 40,000** | 35,000* / 30,000** | | |
| Note: Actual fuel filter service intervals may vary based on fuel quality and vehicle application. For additional information, reference service document 170/Description, Design and Function/Diesel Fuel. | Km | 120,000* / 90,000** | 95,000* / 90,000** | 70,000* / 65,000** | 55,000* / 50,000** | | |
| Note: VAH low capacity oil pan oil drain interval is 20,000 miles. Use severe duty category for all filters. | Hours | 2,000* / 1,600** | 1,700* / 1,600** | 1,400* / 1,300** | 825* / 750** | | |
| MACK PREMIUM EXTENDED-LIFE COOLANT | | | | | | | |
| Mack Premium Extended-Life Coolant (Replace) | Miles | 750,000 | | | | | |
| | Km | 1.200,000 | | | | | |
| | Hours | rs 96 months | | | | | |
| Mack Premium Extended-Life Coolant Filter (Replace) | Miles | | | | | | |
| | Km | | | | | | |
| | Time | 12 months | | | | | |
| MISCELLANEOUS | | | | | | | |

| Valve Adjustment | | | | | | | |
|---|-------|---|--------------------|------------|--|--|--|
| | Km | 240,000 / then every 500,000 | | | | | |
| | Time | 12 months / then every 24 months | | | | | |
| Fan and Accessory Drive Belt and Tensioners (Replace) | Miles | 450,000 | 360,000 | 315,000 | 210,000 | | |
| | Km | 724,000 | 579,000 | 506,000 | 337,000 | | |
| | Time | | 36 months | | 12 months | | |
| Mack Premium Air Filter and Fuel Tank Ventilation Filter (Replace) | Time | Inspect at each oil drain. Replace at max restrictions as indicated on gauge or 24 months. | | | Inspect at each oil drain. Replace at max restrictions as indicated on gauge or 12 months | | |
| EXHAUST AFTERTREATMENT SYSTEM | | Economy Duty | Normal Duty | Heavy Duty | Severe Duty | | |
| Diesel Particle Filter (DPF) - Clean | Miles | 600,000 | 480,000 | 405,000 | 280,000 | | |
| | Km | 965,000 | 772,000 | 650,000 | 450,000 | | |
| | Hours | 15,000 | 12,000 | 10,000 | 5,000 | | |
| DEF, Pump and Tank Filler Neck Filter Drain DEF tank, replace DEF pump main filter, clean DEF tank neck filter. | Miles | 300,000 | 240,000 | 180,000 | 175,000 | | |
| | Km | 482,000 | 386,000 | 289,000 | 280,000 | | |
| | Hours | 9,000 | 7,000 | 5,500 | 5,200 | | |
| TRANSMISSION AND AXLES | | Economy Duty | Normal Duty | Heavy Duty | Severe Duty | | |
| MACK <i>m</i> DRIVE™ TRANSMISSION | | | | | | | |
| <i>m</i> DRIVE; <i>m</i> DRIVE Severe Duty and <i>m</i> DRIVE with Crawler Gears | | | | | | | |
| | | | | 000 | | | |
| Transmission oil and filter (Replace) Oil quality: Mack Transmission Oil 97319 *Applies for <i>m</i> DRIVE severe duty and <i>m</i> DRIVE with Crawler Gears only | Miles | 525,000 | 500,000 800,000 | | 250,000* | | |
| | Km | 844,000 | | 400,000* | | | |
| | Time | 60 months 2,500 hours | | | | | |
| AXLES | | | | | | | |
| Mack Proprietary Rear Axle Oil (Replace) | Miles | 250,000 (GO-J) 500,000 (GO-J PLUS) | | | 40,000 (GO-J) 80,000 (GO-J PLUS) | | |
| | Km | 400,000 (GO-J) 800,000 (GO-J PLUS) | | | 65,000 (GO-J) 125,000 (GO-J PLUS) | | |
| | Time | 24 months (GO-J) 36 months (GO-J PLUS) | | | 1200 hours or 12 months | | |
| Vendor Rear Axle Oil (Replace) | | See axle manufacturer guidelines | | | | | |
| 3 Axle Alignment | Time | 12 months (minimum) | | | | | |
| CHASSIS | | Economy Duty | Normal Duty | Heavy Duty | Severe Duty | | |
| Mack Premium Chassis Lubrication | Miles | | 15,000 | | 10,000 | | |
| | Km | 24,000 | | | 16,000 | | |
| Electrical System Connectors (Check) | Time | Every 6 months | | | | | |
| Power Steering Fluid and Filter (Replace) | Miles | 150,000 | | | | | |
| | Km | 240,000 | | | | | |
| | Time | | 12 months | | | | |
| Air Dryer Coalescing Cartridge (Replace) | Miles | 150,000 | | | | | |
| | Km | 240,000 | | | | | |
| | Time | | 12 months | | | | |
| | | | | | | | |

These maintenance intervals are general recommendations. Please refer to the appropriate maintenance and lubrication manual for your specific vehicle as the authoritative source for all details of a proper and complete inspection and maintenance plan for your vehicle. Recommended intervals by Miles, Km or Hours whichever occurs first.